



Family	Model	Lift Weight kg	Lift Capacity FTG mm	Volts V	Clear Inside Platform Width mm	Clear Inside Platform Length mm	Overall Loader Height mm	Overall Extension of Arc, from stowed position to Maximum Height mm	Overall Loader Width mm	Overall Dimension of outside lift arms Width mm	Overall Loader Depth At handrail height mm	Overall Loader Depth At base with Cover when folded mm	Base Plate length mm	Base Plate Width mm	Kick-out is measured from front of base plate edge to the closest point, for the platform has been lowered down 100mm from floor level mm	Kick-out is measured from the front of base plate edge, to the Rotating Pivot side arm or saddle, at floor level mm	Kick-out is measured from, front of base plate edge to Rotating Pivot side arm or saddle at 100mm down mm	
E-Series	EDEC08V74105L	137	800	400kg	12V	740	1050	1150	+ 25	1085	965	500	430	1000	325	362	410	415

All measurements are to be used as a guide as slight variations may occur between all units

Quick Facts

Two piece split expanded mesh platform • 400kg lifting capacity • Easy access integrated manual back-up pump and handle • Durable hand-held control unit • Dual handles to assist with standee and wheelchair users • Lift-Tite system automatically secures the platform when in transit • Durable ripple black finish • Side or rear door application • Electrohydraulic power up/gravity down operation • Mechanically operated out-board barrier • Equipped with adjustable anti-rattle features to suppress noise during transit • Safety yellow automatic mechanical in-board barrier.